

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
GP	00	M1	REVISED PER ECO-11-004835	11MAR11	RK HMR

① TO PREVENT THREAD STRIPPING, SCREW TORQUE SHOULD NOT EXCEED 9 IN LBS.
 ② TAP HOLE IS 6-32UNC-2B, TWO MIN THREADS.
 ③ TAP HOLE IS M4 X 0.7, TWO MIN THREADS.
 ④ TAP: .000150 TIN-LEAD OVER .000050 NICKEL.
 ⑤ TAP: .000150 TIN OVER .000050 NICKEL.

OBSOLETE	FINISH	HOLE TYPE	SCREW	EMBOSSMENT	PART NUMBER
OBSOLETE	⑤	②	993879-1	YES	9-55558-1
OBSOLETE		②	NO	YES	9-55558-0
SUPERSEDED BY -4	④	③	NO	YES	1-55558-1
		②	993879-1	NO	55558-8
	④	②	NO	NO	55558-7
		②	993879-1	YES	55558-4
		②	NO	YES	55558-3

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J. McCLINTON 1-11-88	TE Connectivity	
DIMENSIONS: INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED:	CHK R. STONE 1-11-88	NAME	
	0 PLC ± -	APVD M. GALLOWAY 1-11-88	TAP, POWER DISTRIBUTION	
	1 PLC ± -	PRODUCT SPEC	SIZE	CAGE CODE
	2 PLC ± -	APPLICATION SPEC	114-11000	00779
	3 PLC ± .008	FINISH	WEIGHT	DRAWING NO
	4 PLC ± -	④/⑤	-	114-11000
	ANGLES ± -	MATERIAL	COPPER ALLOY 725.	RESTRICTED TO
		FINISH		-
				SCALE 4:1 SHEET 1 OF 1 REV M1
				CUSTOMER DRAWING

1471-9 (3/11)

55558

A