

151-40119



Article Number: 151-40119

Description: Push-Button Mount, .25" Hole Dia, .13" Max Panel, .2" Max Tie Width, PA66, White, 100/pkg

Base Data	
Local Order Number	TM1SF10C2
Type	TM1SF
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> • Push Mounts, when used with standard cable ties, provide a permanent bundling solution. • The low profile style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.
Quantity Per	pieces
Product Description	HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for quick installation by pushing the mount through a pre-drilled hole. The low profile head is suitable in space constrained areas.
Short Description	Push-Button Mount, .25" Hole Dia, .13" Max Panel, .2" Max Tie Width, PA66, White, 100/pkg
Product Dimensions	
Length L (Imperial)	0.62"
Length L (Metric)	15.8mm
Fixation Method	with Arrowhead / Push Mount (Mounts)
Width W (Imperial)	0.4"
Width W (Metric)	10.2mm
Cable Tie Width Max. (Imperial)	0.2"
Cable Tie Width Max. (Metric)	5.0mm
Height H (Imperial)	0.18"
Height H (Metric)	4.6mm
Height H2 (Imperial)	0.18"
Height H2 (Metric)	4.6mm
Panel Thickness Max. (Imperial)	0.13"
Panel Thickness Max. (Metric)	3.40mm
Panel Thickness Min. (Imperial)	0.13"

151-40119



Product Dimensions	Panel Thickness Min. (Metric)	3.30mm
	Mounting Hole Diameter D (Imperial)	0.25"
	Mounting Hole Diameter D (Metric)	6.35 mm
	Mounting Hole Diameter D Max. (Imperial)	0.28"
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
UL Recognized (US and Canada)	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100Pieces
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces
	Weight (Metric)	1kg