

148-90028

Article Number: 148-90028



Description: HelaCon Plus Push-In Style Wire Connector, Double Spring, 6-Port, Polycarbonate, Purple, 250/pkg

|           |                       |   |
|-----------|-----------------------|---|
| Base Data | Local Order Number    | 148-90028   |
|           | Type                  | HECP-6  |
|           | Color                 | Violet (VT)   |
|           | Features and benefits | <ul style="list-style-type: none"> <li>• Double Spring Technology for safe, secure and reliable connections</li> <li>• Low Insertion Forces + High Retention Values</li> <li>• Accommodates both solid and stranded wire cores</li> <li>• Polycarbonate Housing for quick visual inspection; Meets UL 92V2 standards</li> <li>• Low insertion forces reduces buckling of stranded wire</li> <li>• Able to combine solid and stranded within same housing</li> <li>• Separate test port for fast, easy confirmation of connection</li> <li>• Quick Fit Insertion relieves installer in difficult spots like overhead installations, eliminates twisting motion and reduces overall assembly and connection time.</li> <li>• Max Current Rating to 24 A</li> <li>• Max Voltage Rating to 600 V (c UL us)</li> </ul> |
|           | Quantity Per          | bag   |
|           | Product Description   | Helacon Plus is a unique push-in wire connector with double spring technology. Double spring design requires less insertion force and delivers superior retention values. Helps alleviate repetitive motion injuries often associated with twist-on style connectors.   |
|           | Short Description     | HelaCon Plus Push-In Style Wire Connector, Double Spring, 6-Port, Polycarbonate, Purple, 250/pkg  |
|           | Product Dimensions    |   |
|           | Length L (Metric)     | 19.0mm  |
|           | Max Current           | 24A   |
|           | Max Voltage           | 600V  |
|           | Number of Conductors  | 6   |
|           | Width W (Imperial)    | 1.12"   |
|           | Width W (Metric)      | 28.35mm   |
|           | Height H (Imperial)   | 0.41"   |
|           | Height H (Metric)     | 10.45mm   |
|           | Depth D (metric)      | 19.0mm  |
|           | Depth D (imperial)    | 0.75"   |

148-90028



|                             |                             |                                   |
|-----------------------------|-----------------------------|-----------------------------------|
| Material and Specifications |                             |                                   |
|                             | Material                    | Polycarbonate (PC)                |
|                             | Material Shortcut           | PC                                |
|                             | Flammability                | UL 94 V2                          |
|                             | Halogenfree                 | Yes                               |
|                             | Operating Temperature       | -22°F to +221°F (-30°C to +105°C) |
|                             | ROHS Compliant              | Yes                               |
|                             | Certification/Specification | UL   ANSI/UL 486-C                |
|                             | UL Listed (US and Canada)   | Yes                               |
| Logistic and Packaging      |                             |                                   |
|                             | Package Quantity (Imperial) | 250                               |
|                             | Package Quantity (Metric)   | 50                                |
|                             | Customs Number(Schedule B)  | 7413009000                        |
|                             | Weight (imperial)           | 3.88lbs                           |