


· Color coded screws available (add color screw suffix to Cat. No.)



.055 [1.4]

(2) PLS

EXTENDED

.718 [18.3]

.197 [5.0]

6-32 x .250 [6.3] L SCREW

6-32 x .250 [6.3] L. SCREW

SPECIFICATIONS

Mounting Detail

Ó

067 [1.7] DIA (2) PLS

.312 [7.9]

.187 [4.7]

.310 [7.9]

.310 [7.9]

.197 [5.0]


.947 [24.1]

4

.060 [1.5] (6) PLS -

Rated: 15 Amps Terminal: .032 (.81) Brass, Matte Tin


Binding Head Screw: Brass, Nickel Plate



.197 [5.0]

· Color coded screws available (add color screw suffix to Cat. No.)

.059 [1.5]




.312 [7.9]

CAT. NO. 7778 (Screw Installed & Captivated)

CAT. NO. 7784 (No Screw Supplied) CAT. NO. 8198 (Screw Supplied Unassembled)

VERTICAL TYPE



CAT. NO. 7791 (No Screw Supplied)

CAT. NO. 8174 (Screw Supplied Unassembled)

.276

[7.0]

CAT. NO. 8195 (Screw Supplied Unassembled)

CAT. NO. 7775 (Screw Installed & Captivated)

CAT. NO. 7785 (No Screw Supplied)

8174

Mounting Detail



PC MOUNT Color coded screws available (add color

screw suffix to Cat. No.)

· Combination drive, binding head screw · Color coded screws

available (add color screw suffix to Cat. No.)

SPECIFICATIONS

Rated: 30 Amps

CAT. NO. 7697 (Screw Supplied Unassembled)

CAT. NO. 7789 (No Screw Supplied) CAT. NO. 7699 (Screw Installed & Captivated)

PRINCIPAL FEATURES

-0

(4) PLS

.073 [1.85] DIA.

-.250 [6.3]

[10.0]


0 0 Ó

0 Ó

.076 [1.93] DIA. (6) PLS

.210 [5.3]


- · Compact, heavy duty design
- · Six snap-in legs for total stability




30 AMP - VERTICAL



[5.0]



10-32 x .375 [9.5] L SCREW



HEAVY DUTY

.470 [11.9]

.060 [1.5] (6) PLS -

Terminal: .045 (1.14) Brass, Matte Tin Plate Screw: Stainless Steel

CAT. NO. 7787 (No Screw Supplied) CAT. NO. 8196 (Screw Supplied Unassembled)

Mounting Detail 000 [5.2] 00

.101 [2.6] DIA. (6) PLS

COLOR CODED SCREW TERMINAL SELECTION GUIDE



Terminal: .032 (.81) Brass, Matte Tin Plate

Binding Head Screw: Brass, Nickel Plate

CAT. NO. 7786 (No Screw Supplied)

CAT. NO. 8197 (Screw Supplied Unassembled)

CAT. NO. 8199 (Screw Installed & Captivated)

Color Coded Screw Terminals provide:

394

- Quick identification
- · Visibility for field service troubleshooting

SPECIFICATIONS

Combination Binding Head:

Standard screw is Brass, Nickel Plate. For painted, color head, add suffix as shown.





COLOR SELECTION: Select desired screw terminal and add color suffix to the screw terminal Cat. No.

HEAD COLOR SUFFIX RED **BLACK** WHITE -4 BLUE -5 GREEN -6 YELLOW -7 NICKEL none

CAT. NO. COLOR SUFFIX Ex: XXXX -X



Refer to page 133 for color screws only

· Available for screw terminals where noted.