All rights strictly reserved	All rights strictly reserved. Reproduction or issue to this
form whatever is not pen	form whatever is not permitted without written authority
Property of FCI. Copyright FCI.	pyright FCI.
В	

PART						CONFIGURATION 120191817161514131211110 9 8 7 6 5 4 3 2 1 1 -																			
NUMBER	ROW	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
88947-XY3LF	d	-	X	_	X	_	_	Χ	-	X	-	Χ	-	X	-	Χ	X	_	X	_	X	_	Х		X
SEE NOTE 11	С	-	X	_	X	_	_	Χ	_	X		Χ	-	Х	-	Χ	X	_	X	_	Х	ı	Х	(– X	X
OPTION	b	-	X	-	X	-	-	Χ	-	X	-	Χ	-	X	-	Χ	X	-	X	-	X	_	X	-	X
OI HON	а	-	X	_	X	_	_	X	-	X	-	Χ	-	X	-	X	X	_	X	_	X	_	X	X	

1 | 2

"X"	=	LOADED POSITION
"—"	=	EMPTY POSITION

PRODUCT NUMBER	PCB THICKNESS	DIM "A"
88947-X02	1.6	2.90
88947-X12	2.4	3.53
88947-X02LF	1.6	2.90
88947-X12LF	2.4	3.53
88947-X03LF	1.6	2.90
88947-X13LF	2.4	3.53

\$

4444

9999 9999

ŎŎŎŎ

ŎŎŎŎ ����

₳₳₳₳

���� ₼₼₼

SEE TABLE 1

| ф | Ø0.10


RECOMMENDED PC BOARD LAYOUT, COMPONENT SIDE.


3.00

2.05+0.05 о ф

1 | 2

1.50+0.10





- - - - -					=
-					
2.00	5.00	4.00	9.50	REF.	

,	TABLE 1
PLATED THRU	HOLE REQUIREMENTS
HOLE DIAMETER AFTER PLATING	0.65-0.80
DRILLED HOLE	0.81-0.86 (0.85 DRILL)
COPPER PLATING	0.025 - 0.05
SnPb PLATING	0.005-0.015
·	

PLATING CONTACT AREA: PERFORMANCE LEVEL TELCORDIA CO CUSTOMER SPECIAL CUSTOMER SPECIAL DASH NR: -1YY/1YYLF -2YY/2YYLF -3YY/3YYLF

47.95 REF. 中国国国国国国 中国国国国国国 中国国国国国国国 中国国国国国国国

3

1.) CONNECTOR MATERIALS:

HOUSING: LCP, 30% GLASS FILLED, UL 94-VO COMPLIANT TERMINAL: PHOSPHOR BRONZE ALLOY

- 2. PRESS-FIT TAIL PLATING: 0.5-1.5 µm TIN LEAD
- 3. PRODUCT SPECIFICATION: GS-12-002
- 4. APPLICATION SPECIFICATIONS: BUS-20-061 GS-20-001 TA-941
- (5) PRODUCT MARKING: (PART NUMBER & LOT CODE).
- (6) INDICATED HOLES ARE UNPLATED.
- (7) DIAMOND LOCATION PEG ARE ONLY EXISTED ON THE BOTH SIDES OF PRODUCT.
- (8) TOP SURFACE OF PRESS BLOCK MAY EXTEND UP TO 0.4MM HIGHER THAN HOUSING. THIS MAY AFFECT THE TAIL LENGTH BEFORE APPLICATION TO A BOARD.
- 9. THESE PRODUCTS WHERE THE PART NUMBER ENDS IN "LF" MEET THE EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.

ALL PRODUCTS WILL WITHSTAND EXPOSURE TO 240°C FOR 60 SECONDS IN A CONVECTION, INFAR-RED OR VAPOR PHASE REFLOW OVEN.

- (10) FOR LEAD FREE PART NUMBERS ADD "LF" SUFFIX. EXAMPLE: 88947-XYYLF.
- (11) ONLY 88947-X03LF AND 88947-X13LF, OTHER P/N IS FULL LOADED

												_												
mat'l. code SEE NOTES				tolerances unless otherwise specified							CUSTOMER			F	C),								
ltr	tr ecn no dr date			;	.x						COPY				=			www.	fcicor	nect.c	om			
М	DG07	'- 0170	Cenh	05/2	2/07	linea	ear .XX		.XX ±.10			proje	ection		title									
N	N DG08-0171 TER 8/15/08		5/08	.XXX ±			.050				B SERIES R/A SIGNAL RECEPT A					PT AS	SSY							
Р	DG09	-0068	Cenh	06/0	6/09	angle	es	0° ±2°				Ž P			4 ROW, 4 MOD, PF						PF	F		
R	DG-C	010933	QinDF	b3/0	8/12	dr	dr STI		STU STONER		10/29/92					ıct fa		MET	RAL	(tm)	cod	е	
						engr	De-	-Feng	Qin	b3/0	8/12	-		-	size	dwg	no					2	13	
						chr	Tian	-Zha	o Lin	03/0	8/12	scale	е		٨		2	20	4	7		shee	et	
						appd	chr Tian-Zhao			03/0	8/12		<u>1:1</u>		Α		0	<u> </u>	7 +	/		1 (of 1	
she		revisi	ion																					
inde	x	shee	t																					
				Cenh 06/06/09 angles O* ±2*						3				(code	F 0 6	,			4			

22526

PDS: Rel (A) STATUS:Released Printed: Mar 26, 2012