ALCOSWITCH ILLUMINATED TACTILE SWITCH SERIES

With Tactile Cap Series

The new ALCOSWITCH Illuminated Tactile switch series is designed for easy operation and reliability in a variety of board mounted applications. The tactile switch includes an LED indicator, available in low and high intensity versions, and 8 unique color options. Rated up to 500,000 electrical lifecycles, the Illuminated Tactile series is designed to last. We offer the translucent caps in two different styles and in five different colors.



Applications

The illuminated tactile switch is well suited for designs requiring illuminated interfaces via pushbutton style switches including:

- Industrial equipment
- Building Automation / HVAC equipment
- Instrumentation
- Communication equipment
- Control equipment

Electrical

• Electrical life

(pushbutton only): 100/160 GF (grams-force):

500,000 cycles

260/520 GF (grams-force):

200,000 cycles

Mechanical

Number of poles:

Switch Functions: OFF-(ON)Contact Rating: 50 mA @ 12 VDC

Product Specifications

- RoHS Directive 2002/95/E compliant
- REACH Compliant and Pb Free

Materials

• Contacts: Stainless Steel, Silver plated

• Actuator: High temperature

Thermoplastic (UL94-V0)


Terminals: Brass, Silver PlatedCase: High temperature

Thermoplastic (UL94-V0)

Key Benefits

- Durability with switches rated up to 500,000 electrical life cycles
- Achieve design flexibility with low or high intensity LED indicators available in 8 color options
- Save board space with integrated superbright LED
- Faster board assembly with reflow or wave solder compatible designs
- Enable ease of use with tactile and audible feedback
- Designed to fit your specific application with a wide range of actuation forces available
- Caps enhance the size of the illumination
- Caps offer an easy type of actuation of the existing switch





For additional product information, including drawings, customer viewable models, and distributor inventory, please visit <u>TE.com</u>. Use the Product Key to determine the desired part configuration, or reference the below Part Selection table.

Product Selection Information

Descriptive PN	Body Style	LED Intensity	LED color	TE PN
FSMIJ61AB04	Illuminated 6x6 Tact, THT	LI	Blue	2213818-1
FSMIJ62AG04	Illuminated 6x6 Tact, THT	LI	Yellow Green	<u>1-2213818-9</u>
FSMIJ63AR04	Illuminated 6x6 Tact, THT	HI	Soft Orange	<u>3-2213818-9</u>
FSMIJ65AB04	Illuminated 6x6 Tact, THT	LI	Blue	4-2213818-9
FSMIJM61AB04	Illuminated 6x6 Tact, SMT	LI	Blue	<u>2213819-1</u>
FSMIJM62BB04	Illuminated 6x6 Tact, SMT	HI	Blue	<u>2-2213819-5</u>
FSMIJM63BB04	Illuminated 6x6 Tact, SMT	HI	Blue	4-2213819-1
FSMIJM65AR04	Illuminated 6x6 Tact, SMT	LI	Red	<u>5-2213819-5</u>
FSMIJ61ASPG04	Illuminated 6x6 Tact, SMT	HI	Pure Green	2213818-2
FSMIJ61AW04	Illuminated 6x6 Tact, SMT	HI	Yellow	2213818-8
FSMIJ61AO04	Illuminated 6x6 Tact, SMT	HI	Red Orange	<u>2213818-6</u>
FSMIJ61AY04	Illuminated 6x6 Tact, SMT	HI	Cold White	<u>2213818-4</u>

LI = low intensity HI = high intensity




Product Selection Information


Switch LED Color	Cap Style	Recommended Cap Color	TE PN Round Cap	TE PN Square Cap
Blue		Blue	2311402-4	2311403-4
Pure Green	•	Green	2311402-1	<u>2311403-1</u>
Yellow Green	•	Yellow	2311402-5	<u>2311403-5</u>
Yellow Green	•	Green	2311402-1	<u>2311403-1</u>
Yellow	•	Yellow	<u>2311402-5</u>	<u>2311403-5</u>
Soft Orange	•	Red	2311402-3	<u>2311403-3</u>
Red Orange		Red	2311402-3	2311403-3
Red	•	Red	2311402-3	2311403-3
Cold White	•	Black	2311402-2	2311403-2

The tactile cap series is sold separately

Part Number 2311402



Part Number 2311403





te.com

© 2017 TE Connectivity Ltd. Family of Companies. All Rights Reserved. ALCOSWITCH, TE, TE Connectivity, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and Company names mentioned herein may be trademarks of their respective owners.

1-1773878-5 BH 1/2017

USA: +1 (800) 522-6752 Canada: +1 (905) 475-6222 Mexico: +52 (0) 55-1106-0800 Latin/S. America: +54 (0) 11-4733-2200 Germany: +49 (0) 6251-133-1999 UK: +44 (0) 800-267666 France: +33 (0) 1-3420-8686 The Netherlands: +31 (0) 73-6246-999 China: +86 (0) 400-820-6015

