



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS)
BF22312-45B	x = 0.273 y = 0.237	1160 @ 0°C	750	5.0	30,000 ± 20%	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS  TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- 0	<b>JKL COMPONENTS CORPORATION</b>					
		TITLE <b>MINIATURE COLD CATHODE FLUORESCENT LAMP</b>					
DRAWN BY L. WENGSTROM	APPV'D BY L.R.	DATE 6/3/08	SIZE <b>A</b>	FSCM NO. <b>55335</b>	DRAWING NO. <b>BF22312-45B</b>		
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 6/3/08	REVISION DATE	REV. NO.	SHEET 1 OF 1

REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE
RELEASED		6/3/08