Mallor Mallor	lory Sonalert Products, Inc.			Part #: JT120-RY-CD		
Sales Outline Drawing				Revision:	В	
Specifications:						
Stack Number:	1	2				
LED Color:	RED	YELLOW				
Connection Wires:	Red and Brown	Yellow and Brown				
LED Current Draw:	<210mA	<230mA				
Rated Voltage:	120 VAC					
Operating Voltage:	90-120 VAC					
Total Max Current:	<440 mA					
Operating Temperature:	-25° ~ +60°C					
Lens Color:	Opaque White					
Material:	ABS FR15U					
Mounting Method:	Direct Mount using 1/2" NPT Stainless Steel Pipe and Nut					
Weight Typical (g):		210				
NEMA 12:	Approved					
Options:		Please contact factory.				
Dimensions: Inches		cUL Recognized			ROHS Compliant	
	4.5	YELLOW (114.3)	00.88 [ø22.2]	8" ire		
		2.4 [61.8]	KNOCK OUT - FOR WIRES	MOUNTING DIAGRAM		
LED OPERATION: CONN	IECT STACK COL	OR WIRE TO POWER A	ND BROWN WIRE	TO POWER		
LED OF EINATION. JOONIN	LOT STACK GOL	ON WINE TO LOWER A	DINOVVIN VVIINI	- TO TOVVLIX.		