

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



EVO connector set, B16 series, metal housing, consisting of sleeve housing 1411461, panel mounting base 1411325, EVO screw connection 1411446, pin contact insert 1407732, socket contact insert 1407731



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	680.0 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

General

Number of positions	16+PE	
Туре	B16	
Cable exit	straight	
Degree of protection for housing	IP66	
	IP69K (ISO 20653:2013-02)	
	IP66 (with closed protective cover)	
	4	
	4X	
	12	
Connection method	Push-in connection	
Rated voltage (III/3)	500 V	
Rated surge voltage	6 kV	
Rated current	16 A	

Standards and Regulations

EL 133 C C C 14 04	1.00
Flammability rating according to UL 94	V0



Articles in set

Contact insert - HC-B 16-I-PT-F - 1407731



HEAVYCON socket insert, B16 series, 16 + PE-pos., push-in connection

Contact insert - HC-B 16-I-PT-M - 1407732



HEAVYCON pin insert, B16 series, 16 + PE-pos., push-in connection

Housing - HC-STA-B16-BWSC-ELC-AL - 1411325



HEAVYCON B16 panel mounting base, with single locking latch, with plastic protective cover, with flat gasket, salt-water-resistant aluminum, conductive profile gasket.

Housing - HC-EVO-B16-HHFS-EL-AL - 1411461



HEAVYCON EVO sleeve housing, EMC version, without powder coating, with bayonet flange for EVO screw connection, B16, for single locking latch, height: 88 mm, without EVO screw connection.

Cable gland - HC-B-G-M25-EC-AL - 1411446



EVO EMC cable gland with bayonet locking, B series, size M25, cable diameter: 11 - 16 mm



Classifications

eCl@ss


eCl@ss 5.1	27143424	
eCl@ss 6.0	27143424	
eCl@ss 8.0	27440101	
ETIM		
ETIM 4.0	EC002641	
ETIM 5.0	EC002636	
Approvals		
Approvals		
Approvals		
EAC / EAC		
Ex Approvals		
Approvals submitted		
Approval details		
EAC		

Drawings


EAC




Schematic diagram



Schematic diagram




Pin assignment, connection side, pin



Pin assignment, connection side, socket


Dimensional drawing



Derating diagram

Dimensional drawing

Dimensional drawing



Panel cutout

Phoenix Contact 2016 © - all rights reserved http://www.phoenixcontact.com