

## Cable gland - G-INB-M25-M68N-NEPDS-S - 1415183

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Nickel-plated brass, Application: Standard, External cable diameter 9 mm ... 17 mm, Shielding: No, Connecting thread: M25, Color: silver



### Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
Custom tariff number	74199990
Country of origin	Germany

### Technical data

#### Dimensions

Length	120 mm
Length without connecting thread	113 mm
Connecting thread diameter	25 mm
Wrench size, union nut	29 mm
Wrench size, support	29 mm
Hexagon angular dimension GRP	32 mm
Length of the connecting thread	7 mm
External cable diameter	9 mm ... 17 mm

#### Ambient conditions

Degree of protection	IP68 (5 bar / 0.5 h)
	IP69K
Ambient temperature (operation)	-40 °C ... 100 °C (dynamic)

#### General

Cable gland material	Nickel-plated brass
Seal material	EPDM

# Cable gland - G-INB-M25-M68N-NEPDS-S - 1415183

## Technical data

### General

Shielded	No
Thread type on connection side	M25
Color	silver

## Classifications

### eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109

### ETIM

ETIM 5.0	EC000441
----------	----------

## Approvals

### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / GOST-R / cULus Recognized

---


#### Ex Approvals


---

#### Approvals submitted

---

### Approval details


UL Recognized 
---

cUL Recognized 
--

# Cable gland - G-INB-M25-M68N-NEPDS-S - 1415183

## Approvals

GOST-R 

cULus Recognized 

## Drawings

Dimensional drawing

